






VML106

Switch Disconnector Incomer

Characteristics:

- All Design 10 consumer units contain top, bottom & rear knockouts and a meter tail cable entry plate (**VM04CE**) as standard- see page 38 for knockout sizes.
- Supplied with a full metal DIN rail, 100A switch disconnector incomer and a full complement of earth and neutral terminals along with marking labels, busbar and instructions.
- References ending in **SPD** come with a Type 2 SPD fitted.
- Recommended for use with TT systems when utilising RCBO on all outgoing circuits.
- We also recommend the use of cable clamp (**VA10MT**) for use on TT systems, available as an accessory.
- Conforms to BS EN 61439-3 Including Annex ZB (16kA rating).
- For accessories see page 32, for dimensions see page 38, refer to board sizes below.



Description	Size	Cat ref.	Cat ref. With Round Knockouts
2 Way 63A Switch Disconnector Incomer	2	VML202	VML202RK
6 Way 63A Switch Disconnector Incomer	3	VML206	VML206RK
6 Way 100A Switch Disconnector Incomer	3	VML106	VML106RK
10 Way 100A Switch Disconnector Incomer	4	VML110	VML110RK
14 Way 100A Switch Disconnector Incomer	5	VML114	VML114RK
20 Way 100A Switch Disconnector Incomer	7	VML120	VML120RK
8 Way 100A Switch Disconnector Incomer with Factory Fitted Surge Protection	4	VML108SPD	VML108SPDRK
12 Way 100A Switch Disconnector Incomer with Factory Fitted Surge Protection	5	VML112SPD	VML112SPDRK
18 Way 100A Switch Disconnector Incomer with Factory Fitted Surge Protection	7	VML118SPD	VML118SPDRK
6 + 6 Way Dual Row 100A Switch Disconnector Incomer	3 (2)	VML10606	-
10 + 10 Way Dual Row 100A Switch Disconnector Incomer	4 (2)	VML11010	-
14 + 14 Way Dual Row 100A Switch Disconnector Incomer	5 (2)	VML11414	-
20 + 20 Way Dual Row 100A Switch Disconnector Incomer	7 (2)	VML12020	-
8 + 10 Way Dual Row 100A Switch Disconnector Incomer with Factory Fitted Surge Protection	4(2)	VML10810SPD	-
12 + 14 Way Dual Row 100A Switch Disconnector Incomer with Factory Fitted Surge Protection	5(2)	VML11214SPD	-
18 + 20 Way Dual Row 100A Switch Disconnector Incomer with Factory Fitted Surge Protection	7(2)	VML11820SPD	-



VML310AH

RCCB Incomer

Characteristics:

- All Design 10 consumer units contain top, bottom & rear knockouts and a meter tail cable entry plate (**VM04CE**) as standard- see page 38 for knockout sizes.
- Supplied with a full metal DIN rail, 40A, 63A or 100A 30mA Type A RCCB incomer and a full complement of earth and neutral terminals along with marking labels, busbar and instructions.
- Conforms to BS EN 61439-3 Including Annex ZB (16kA rating).
- For accessories see page 32, for dimensions see page 38, refer to board sizes below.



Description	Size	Cat ref.	Cat ref. With Round Knockouts
2 Way 63A 30mA Type A RCCB Incomer	2	VML402AH	-
6 Way 63A 30mA Type A RCCB Incomer	3	VML406AH	-
10 Way 63A 30mA Type A RCCB Incomer	4	VML410AH	-
6 Way 100A 30mA Type A RCCB Incomer	3	VML306AH	VML306AHRK
10 Way 100A 30mA Type A RCCB Incomer	4	VML310AH	VML310AHRK
14 Way 100A 30mA Type A RCCB Incomer	5	VML314AH	VML314AHRK